



RE: Third West air monitor results Shepherd, Michael to: Joyce Ackerman

09/07/2011 11:29 AM

Cc: "Clegg, Benjamin M.", "Craig Barnitz (cbarnitz@utah.gov)"

From:

"Shepherd, Michael" < Michael. Shepherd@PacifiCorp.com>

To:

Joyce Ackerman/R8/USEPA/US@EPA

Cc:

"Clegg, Benjamin M." <Benjamin.Clegg@PacifiCorp.com>, "Craig Barnitz (cbarnitz@utah.gov)"

<cbarnitz@utah.gov>

1 attachment

219459-1,2.pdf

Joyce,

It was Chrysotile. The data sheet is page 4 of the attached report.

Thanks,

Mike Shepherd 801.220.4584 Office 801.631.1310 Cell

----Original Message----

From: Ackerman.Joyce@epamail.epa.gov [mailto:Ackerman.Joyce@epamail.epa.gov]

Sent: Wednesday, September 07, 2011 10:25 AM

To: Shepherd, Michael

Cc: Clegg, Benjamin M.; Craig Barnitz (cbarnitz@utah.gov)

Subject: Re: Third West air monitor results

Hi Mike - I noticed on page 2 of this report that there were some fibers detected, although too few to be registered above the lab's reporting limit. I didn't see the data sheet for these samples. Is it available to see what kind of fibers were seen by the lab (e.g., chrysotile,

tremolite, etc.)?

Thanks!

Joyce Ackerman, On-Scene Coordinator EPA Region 8 1595 Wynkoop St. Denver, CO 80202 Phone: 303-312-6822

From: To:

"Shepherd, Michael" <Michael.Shepherd@PacifiCorp.com> "Craig Barnitz (cbarnitz@utah.gov) " <cbarnitz@utah.gov>,

Cc:

Joyce Ackerman/R8/USEPA/US@EPA

Date:

"Clegg, Benjamin M." <Benjamin.Clegg@PacifiCorp.com> 09/02/2011 09:19 AM

Subject:

Third West air monitor results

Craig and Joyce,

Attached are the air monitoring results for the past week. All results came back negative.

Thanks,

Mike Shepherd
Project Manager
Rocky Mountain Power - Major Projects
801.220.4584 Office
801.631.1310 Cell
801.220.2797 Fax
michael.shepherd@pacificorp.com[attachment "219459-1.pdf" deleted by
Joyce Ackerman/R8/USEPA/US]



September 7, 2011

Laboratory Code:

RES

Subcontract Number:

NA

Laboratory Report: Project # / P.O. #

RES 219459-1,2 None Given

Project Description:

3rd West Substation

David Roskelley R & R Environmental 47 West 9000 South #2 Sandy UT 84070

Dear Customer,

Reservoirs Environmental, Inc. is an analytical laboratory accredited for the analysis of Industrial Hygiene and Environmental matrices by the National Voluntary Laboratory Accreditation Program (NVLAP), Lab Code 101896-0 for Transmission Electron Microscopy (TEM) and Polarized Light Microscopy (PLM) analysis and the American Industrial Hygiene Association (AIHA), Lab ID 101533 - Accreditation Certificate #480 for Phase Contrast Microscopy (PCM) analysis. This laboratory is currently proficient in both Proficiency Testing and PAT programs respectively.

Reservoirs Environmental, Inc. has analyzed the following samples for asbestos content as per your request. The analysis has been completed in general accordance with the appropriate methodology as stated in the attached analysis table. The results have been submitted to your office.

RES 219459-1,2 is the job number assigned to this study. This report is considered highly confidential and the sole property of the customer. Reservoirs Environmental, Inc. will not discuss any part of this study with personnel other than those of the client. The results described in this report only apply to the samples analyzed. This report must not be used to claim endorsement of products or analytical results by NVLAP or any agency of the U.S. Government. This report shall not be reproduced except in full, without written approval from Reservoirs Environmental, Inc. Samples will be disposed of after sixty days unless longer storage is requested. If you have any questions about this report, please feel free to call 303-964-1986.

Sincerely,

Jeanne Spencer Orr

President

RESERVOIRS ENVIRONMENTAL, INC.

AIHA Certificate of Accreditation #480, Lab ID 101533

TABLE: PCM NIOSH 7400 FIBER COUNT ANALYSIS

RES Job Number:

RES 219459-1,2

Client:

R & R Environmental

Client Project Number / P.O.:

None Given

Client Project Description:

3rd West Substation

Date Samples Received:

August 25, 2011

Analysis Type:

PCM 7400 A, Issue 2

Turnaround:

3-5 Day

Date Samples Analyzed:

August 30, 2011

Client ID Number	Lab ID Number	Air Volume Sampled	Fields Analyzed	Fiber Count	Reporting Limit	Fiber Density	Reporting Limit	Fiber Concentration
		(L)			(F/mm²)	(F/mm²)	(F/cc)	(F/cc)
3W-081911-N	EM 786508	1156	100	1	7.01	BRL	0.002	BRL
3W -081 9 11-E	EM 786509	1152	100	2.5	7.01	BRL	0.002	BRL
3W-081911-S	EM 786510	758	100	. 0	7.01	BRL	0.004	BRL ·
3W -081 9 11- W	EM 786511	49 6	100	1	7.01	BRL	0.005	BRL

^{*} Unless otherwise stated sample analyses have been blank corrected.

Laboratory Quarterly Coefficient Variation (CV) by Fiber Count Range

- April 1, 2011 - June 30, 2011

5-20 CV = 0.26

>20-50 CV = 0.20

>50-100 = 0.14

Digitally signed by Gina Vettraino Date: 2011.09.07 08:30:22 - 06:00

RESERVOIRS ENVIRONMENTAL, INC.

NVLAP Lab Code 101896-0; TDH: #30-0015

TABLE I. TEM AIR FILTER SAMPLE DATA AND ANALYTICAL RESULTS

RES Job Number:

. RES 219459-1,2

Client:

R & R Environmental

Client Project Number / P.O.: None Given

3rd West Substation

Client Project Description: Date Samples Received:

August 25, 2011

Analysis Type:

TEM, AHERA

Turnaround:

3-5 Day

Date Samples Analyzed:

August 31, 2011 & September 6, 2011

Client ID Number	Lab ID N	umber	Area Analyzed	Air Volume Sampled	Number of Asbestos Structures Detected	Analytical Sensitivity	Asbestos Concentration	Filter Loading
			(mm²)	(L)		(s/cc)	(s/cc)	(s/mm²)
3W-081911-N	EM	786508	0.0770	1156	1	0.0043	0.0043	13 .0
3W-081911-E	EM	786509	0.0770	1152	ND	0.0043	BAS	BAS
3W-081911-S	EΜ	786510	0.1100	758	ND	0.0046	BAS	BAS
3W-081911-W	EM	7865 11	0.1100	496	ND	0.0071	BAS	BAS
3W-082211-N	EM	7865 12	0.0990	87 2	ND	0.0045	BAS	BAS
3W -08 2211- E	EM	7865 13	0.1100	874	ND	0.0040	, BAS	BAS
3W-082211-S	EM	786514	0.0990	876	ND	0.0044	BAS	BAS
3W-082211-W	EM	786515	0.0990	874	ND	0.0044	BAS	BAS
3W-082311-E	EM	786516	0.0880	888	ND	0.0049	BAS	BAS
3W-082311-S	EM	786517	0.0880	884	ND	0.0049	BAS	BAS
3W-082311-W	EM	786518	0.0880	884	ND	0.0049	BAS	BAS
3W-082311-N	EM	786519	0.0880	880	ND	0.0050	BAS	BAS
3W -08 2 411-S	. ЕМ	7865 2 0	0.0880	916	ND	0.0048	BAS	BAS
3W-082411-E	EM	7865 21	0.0880	916	ND	0.0048	BAS	BAS
3W-082411-N	EM	7865 22	0.0880	89 2	ND	0.0049	BAS	BAS
3W-082411-W	EM	7865 23	0.0880	908	ŅD	0.0048	BAS	BAS

NA = Not Analyzed

ND = None Detected

BAS = Below Analytical Sensitivity

Average Grid Opening in mm² = 0.011

Filter Material = Mixed Cellulose Ester

Filter Diameter = 25 mm

Effective Filter Area = 385 sq mm

DATA QA

RESERVOIRS ENVIRONMENTAL, INC.

NVLAP Lab Code 101896-0; TDH: #30-0015

TABLE II. SUMMARY OF ANALYTICAL DATA

RES Job Number:

RES 219459-1,2

Client:

R & R Environmental

Client Project Number / P.O.: None Given

Client Project Description:

3rd West Substation

Date Samples Received:

August 25, 2011

Analysis Type:

TEM, AHERA

Turnaround:

3-5 Day

Date Samples Analyzed:

August 31, 2011 & Septer

Ciient Lab ID Number ID Number		Asbestos Mineral				<u></u>	Structures >5 Microns	**Excluded Structures	Asbestos Structures		
			_	Asl	oestos Str	ucture Typ	oes* ·	in Length		for	
				Fibers	Bundles	Clusters	Matrices			Concentration	
3W-081911-N	EM	786508	Chrysotile	0	0	0	1	0	0	1	
3W-081911-E	EM	7 8 650 9	ND	0	0	0	0	0	. 0	0	
3W-081911-S	EM	786510	. ND	0	0	0	0	0	0	0	
3W-081911-W	EM	7 8 65 11	ND	0	0	0	0	0	0	0	
3W-082211-N	EM	7 8 65 12	ND	0	0	0	0	0	0	0	
3W-082211-E	EM	7 8 65 13	ND	0	0	0	0	0	0.	0	
3W-082211-S	EM	7 8 65 14	ND	0	. 0	0	0	0	0	. 0	
3W-082211-W	EM	7 8 65 1 5	ND	0	0	0	0	0	.0	0	
3W-082311-E	EM	7 8 65 1 6	ND	0	0	0	0	0	. 0	0	
3W-082311-S	EM	7 8 65 1 7	ND	0	0	0	0	0	0	. 0	
3W-082311-W	EM	7 8 65 18	. ND	0	0	0	0	0	0	0	
3W-082311-N	EM	7 8 65 19	ND	0	0	. 0	0	0	0	0	
3W-082411-S	EM	7 8 65 2 0	ND	0	. 0	0	0	0	0	. 0	
3W-082411-E	EM	7 8 65 21	ND	0	0	. 0	0	0	0	0	
3W-082411-N	EM	7 8 65 22	. ND	0	0	0	0	0	0	0	
3W-082411-W	EM	7 8 65 23	ND	0	0	0	0	0	0	0	

^{*}See Analytical Procedure for definitions

^{**}C = Excluded from total due to lack of confirmation

^{**}L = Excluded from total for length less than 0.5 micron (AHERA only)

^{**}A = Excluded from total due to incorrect aspect ratio

ND = None Detected

Due Time:

Reservoirs Environmental, inc. 5801 Logan St. Denver, CO 80216 • Pit. 303 964-1988 • Fax 303-477-4276 • Toll Free :898 RESI-ENV

Pager: 303-809-2468 INVOICE TO: (IF DIFFERENT) **CONTACT INFORMATION:** Contact Dave Roskelly . * R Environmental Contact Justin Kars is Phone: 801 541-1035 ddress: 47 W. 9800 S Sandy 14. 840TD Call/pager Preject Number moler P.O. 6: Finel dan Ossumbhi Ermil Addnes: Mave & Mensiro. com Project Oescription/Lecation: 3RD West Substation I with e receivo.com REQUESTED ANALYSIS VAUD MATRIX CODES ASBESTOS LABORATORY HOURS: Weekdays: 7am - Tpm LAB NOTES RUSH (Same Day) PRIORITY (Next Day) STANDARD Air = A Bulk = B (Rush PCM = Mir, TEM = 6ir.) Dust = D Paint = P CHEMISTRY LABORATORY HOURS: Weekdays: Sam - Spm Soli = S Wipe = W Metai(s) / Dust ___RUSH ___ 24 hr. ___ 3-5 Day Swab = 6W F = Food **Prier notification is RCRA 8 / Metals & WMding Drinking Water = DW Wasta Water = WW 3 Point Count required for RUSH RUSH ___ 5 day ___10 day Fume Scan / TCLP Q = Other * S turnareunde.** Organics 24 hr. ___ 3 day ___5 Day **ASTM E1792 approved wipe media only** <u>S</u> MICROBIOLOGY LABORATORY HOURS: Weekdays: 9am - 5pm METALS - Analyte(s) RCRA 8, TCLP, Welding Fume. OSHA E.coll O1B7:H7. Coliforms, S.aureus ____ 24 hr. ____2 Day 3-6 Day Salmonella, Listeria, E.cell, APC, YAM 48 Hr. 3-S Day RUSH 24 Hr MoM 48 Hr 3 Day [™]Tumarsund times establish a jaboratory priority, subject to jaboratory vo**lume** and are not guaranteed. Additional Fees Sample Volume apply for atternouns, weekends and holidays." # Containers Watrix Code Special Inatructions: EM Number (Laborato Date Time Use Only) Collected Collected Client sample ID number (Sample ID's must be unique) mm/dd/yy hh/mm e/o 3W-081911-N 8/19/11 156 786508 3W-081911-E 152 3w -081911- 5 36-081911-W 496 3111-082211- M 872 3W-082211-F 13 361-0822U - 61 15 ક્ષેટરીય 13W-0823H -384 10|3W-082311 - S Number of samples received: (Additional samples shall be listed on attached long form.) NOTE: RE will analyze incoming sample) based agon Intograted reserved and will not be responsible for errors or omissions in calculations essuting from the inaccuracy of original data. By eigning clerat/company representative agrees that submission of the following samples for requested enetysib as indicated on thit Cham of Custody shall constaute an antityteal services agreement wim payment tarms of NET 30 days, failure to comply with payment tarms not present tarms of NET 30 days, failure to comply with payment tarms not present tarms of NET 30 days, failure to comply with payment tarms not paymen Relinquiched By: Date/Time: Sample Condition: On los Sealed Intact Laboratory Use Only Temp. (F°) Yes / No Yes / No Ym / No Date/Time: Received By: Carrier Results: Contact Phone Email Fax Date Time initials Contact Phone Email Fax Date Time Initials Phone Email Fax Phone Email Fax Contact Date Time Initials Contact Time Initials

4398

Due Date: 838



Pager: 303-509-2098

	<u></u>		INVOICE TO: (IF DIFFERENT)					CONTACT INFORMATION:													
Company: 2	· R		Company:					Contact Comact													
Addness:	<u> </u>	Addre	Address:											Phona							
							Fax:	International Control of the Contr													
			<u> </u>				`	Cell/pager Final Gau Celiveratire Emai Address:													
Project Number		 					Final	Oau Oelve	ratrie Em	nal Ad	dress:									•	
Project Descript	ionAccetion: 32 West Subs	lation continu	ls .																		
ASBESTO	S LABORATORY HOURS: Weekdays	; 7am - 7pm		1		R	EQUE	STED A	NALY	YSIS			. :		VAL	JD M	ATRIX C	ODES	L	B NOT	ES:
PLM / PCM			STANDARD			П				П	П				\ir =	A	E	lul k = B	Ι		
		2hr, TEM = 6hr.)	····-	11		1-1	11	11	1 1	1 [11	1	}		ust =			aint = P	 		
	RY LABORATORY HOURS: Weekday			1	- i		11		∤ ∤,	Ш					ioil =		_	ipe = W			
Metal(s) / D			Prior notification Is	1	[11	11	_e	Н	11		j		ab =			= Food	—		
Fume Scan	letals & WeldingRUSHS		required for RUSH	Point Count	3	1 1	5	11	Catio	Н		툁	y,	Drinking	y Wal			Waler = WW	┼──		
Organics	•-	day5 Day	turnarounds.**	[일	- g		퇇		is s		_	uentification	15	O = Other **ASTM E1792 approved wipe media only**				 			
MICROBIC	DLOGY LABORATORY HOURS: Weel				2 g		- Analyte(s) TCLP, Welding Fume, Metals Scan		ક	إ	Quantification	or Quantification Identification, Quantificati	S.		1	ΓŤ	,		+-		
E.coll 0157		24 hr2 Day3	3-5 Day	7402 E	. 49		햩		ঠ	ig s			Ĕ	l							
	, Usterla, E.coll, APC, Y & M	48 Hr3-5 Day	·		SO-th	용	3		🗦	Quantifica	or Quantific		8	Î	1			İ	1		
Mold		RUSH24 Hr48 H	r3 Day5 Day	ort, Lang		Respirable	[©] 흍	‡	뒽		5 2	충	ဗ					1			
~Tumarouni	I times establish a laboratoly priority, subject to la	boratoly voluine and are not	gilaranteed. Additiotut fees		77 1 1	2	₹ ₹	<u> </u>	ŭ	= -		일	Į ₹	gg .							
	apply for afterhours, vieek	and holidays.**		ş ş	₹ 8	夏	불원	onella: +/-	P 4			* <u>.</u>	Z	돌	<u>.</u>	g.		-	. 1:		
Special Inst	tructions:	· · · · · · · · · · · · · · · · · · ·		Short report,	7400A,	- 78 88	. ¥	Selmonella: +/- E.coil O157:H7:	흥성	E.coft +/-	Saureus:	Y & M: +/- or Quanti Mold: +/-, Identificati	ER	× g	စိုဝ	Containers		l _	EM Nu	mber (L	aboretory
					<u>\$</u>		METALS RORA 8		Aen Aen	и с	3 3	5 S	킾	Ř ₹	Matrix	5	Date Collected	Time Collected		Use Only)	
Client sat	mple ID number (Sample	ID's must be Uniqua)		PLM	Se Se	DUST	발문	5	MICRO				₹S	Sample Volume (L) / Area	₹	#	mm/dd/yy	hh/mm a/p	<u> </u>		
1 3W-0	082311 - W			×	C									834	A		,		7.8	651	18
2 3W 1	982311 - N				1,1		·							380				- T	11.		(T
3 3W-0	82411-5									П	\prod			916	Γ					7	20
	32411- E									П	П			916							21
	82411- N									П	\prod	\top		892		$\neg \top$					2 z
	82411-W			Π.							\sqcap			908							23
7	3,0	· · · · · · · · · · · · · · · · · · ·										T									
8							·	+++		H		11	: :	1 11		_				· · · · ·	
9	<u></u>									H	#	Ħ				-		· · · · · · · · · · · · · · · · · · ·			
10						1				\vdash	+		. 1.								7 .
	amples received:	(Additional es	amples shall be listed on	attache	d lone !!	brm)				Щ.	1: 1	_:_1		l	لنسيا		<u> </u>	L	<u> </u>		
NOTE: RE	i will analyze incoming samples based upon information	lacehed and will r ot be respons	alle lor orrors or omissions in ca	dculation:	s resulting	from the									agre	es that	submission of	the foGoving sa	mples for re	quested	
anatysb as	s indicated on this Chain of Custody shall consiltute an a	nalytical services agreement with	payment tenns of NET 30 days	s, fallure t	to comply	with pay	meni tenr	a may resu	t in a 1.	5% m	onthly in	terest	surcheig	0.			· · · · · · · ·				
Relinquis	shed By:				Oat	te/Tim	e :							San	nple	Cond	ition: (On Ice S	Sealed	Intaci	.
Laborato	ry Use Only		ne: 45251/					1	A						•				es / No	Yes /	
Received By Results:		Date/Tim					arrier:				<u> </u>			Data							
	Contact Phone Email Fax		Time Initia		Contac				Ema					Date			Tim		Initia		

Attachment I

Key to Count Sheets
Count Sheets
Analytical Procedures

Structures identifications consist of an Asbestos Type followed by a Structure Type

Asbestos Type

Structure Types

Α	=	Amosite	F =	Fiber
An	=	Anthophyllite	B =	Bundle
C	=	Chrysotile	C =	Cluster
Cr	=	Crocidolite	M =	Matrix
T	=	Tremolite		

ND = no structures detected

d = other structure associated with a matrix

NAM = Non Asbestos Mineral

XGB = partly obscured by a grid bar

Sizing Conversion


1 length unit = 5 mm on screen = 0.278 micron 1.80 length units = 0.5 micron

18.0 length units = 5 microns

1 width unit = 1 mm on screen = 0.0556 micron

TEM Analysts

Jeanne S. Orr Nathan DelHierro Angela Heitger Jonathan Bernard Paul D. LoScalzo Mark Steiner Norberto Zimbleman Robert Workman



Upper and lower 95% confidence bounds for the number of structures counted assuming a Poisson distribution.

Laboratory name:	REI
Instrument	JEOL 100 N S
Vollage (KV)	100 KV
Magnification	20fX 10KX
Grid opening area (mm2)	0.011
Scale: 1L =	0.28 um
Scale: 1D =	0.056 um
Primaiy filter area (mm2)	385
Secondary Filter Area (mm2)	
QA Туре	

Client :	RAR
 Sample Type (A=Air, D=Dust):	A
Air volume (L) or dust area (cm2)	1156
Date received by lab	8/25/11
Lab Job Number.	219459
Lab Sample Number.	786508

Analyzed by	1K
Analysis date	9/6/11
Method (D=Direct, l=Indirect, IA=Indirect, ashed)	D
Counting rules (ISO, AHEFIA, ASTM)	A1+
Grid storage location	Month Analyzed
Scope Alignment	Date Analyzed

F-Factor Calculation (Indirect Preps Only):								
Fraction of primary filter used								
Total Resuspension Volume (ml)								
Volume Applied to secondary filter (ml)	†							

Grid	Grid Opening	Structure	No. of St	ructures	Dime	nsions	Identification	Mineral Class				1 = yes, blank = no		
Olid	Ond Opening	Туре	Primary	Total		Width	Identification	Amphibole	С	NAM	Sketch/Comments			EDS
A	F4-1	M												
	24-1	MD			-	·						,		
	C4-1	NO					·							<u></u>
	134-1	ND		· 	Prep	A	~90/. IV	wact ~	1.	lebri	٥			
B	961	M			2	}	COX				Ship .	·		
	F6-1	M												
	26-1	M									·			
				·	lner	B~	A	Jen f.	200	~ 9	16/11			
		_												
	·													

Laboratory name:.	REt
Instrument	JEOL 100 N S
Voltage (KV)	100 KV
Magnification	20KX 10KX
Grid opening area (mm2)	0.011
Scale: 1L =	0.28 um
Scale: 1D =	0.056 um
Primary filter area (mm2)	385
Secondary Filter Area (mm2)	
QA Type	

I EN Maneatos Off	acture Count
Client :	RIR
Sample Type (A=Alr, D=Dust):	A
Air volume (L) or dust area (cm2)	1152
Date received by lab	8/25/11
Lab Job Numtier.	219459
Lab Sample Number:	786509
	. ,

F-Factor Calculation (Indirect Preps	Only):
Fraction of primary filler used	
Total Resuspension Voluma (ml)	
Volume Applied to secondary filter (ml)	

Analyzed by	1K
Analysis date	9/6/11
Method (D=Dlrect, l=Indirect, IA=Indirect, ashed)	D
Counting rules (ISO, AHERA, ASTM)	AH
Grkl storage location	Month Analyzed
Scope Alkinment	Date Analyzed

Grid	Grid Opening	Structure	No. of Str	uctures	Dime	imensions identification		identification Mineral Class				1 = yes, blank = no		
		Туре	Primary	Total	Length	Width	1	Amphibole	c	NAM	Sketch/Comments	Sketch	Photo	EDS
A	64-3	NO												
	F4-3	10												
	E4-3	ND						_						
	C4-3	10			fr	er A	~80/	. intact	5-10	7. De	bris			
B	24-4	MD												
	C4-4	MD												
	B4-4	NO			Pn	ep	BNA	Je	n	Kn	n Steel	11		
								7			•			
								·						

Laboratory name:	REI
Instrument	JEOL 100 NS
Voltage (KV)	100 KV
Magnification	(2019X IOKX
Grid opening area (mm2)	0.011
Scale: 1L =	0.28 um
Scale: tD =	0.056 um
Primary filter area (mm2)	385
Secondary Filter Area (mm2)	
QA Type	

Client :	P+P
Sample Type (A=Air, D=Dust):	A
Air volume (L) or dust area (cm2)	758
Date received by lab	9/75/1
Lab Job Number:	219459
Lab Sample Number	786510

F-Factor Calculation (Indirect Preps Only):							
Fraction of primary filter used							
Total Resuspension Volume (ml)							
Volume Applied to secondary filter (ml)							

Analyzed by	AF AH
Analysis date	9/6/11
Method (D=Dlrect, l=Indirect, IA=Indirect, ashed)	D
Counting rules (ISO, AHERA, ASTM)	Alt
Grid storage location	Month Analyzed
Scope Alignment	Date Analyzed

Grid	Grid Opening	Stmcture	No. of St	ructures	Dime	nsions	Identification	Mineral Class				1 = ves, blank = no		
		Type	Primary	Total	Length	WMth		Amphibole	С	NAM	Sketch/Comments	Sketch	Photo	EDS
A	E3-1	CN												
	Carl	ND												
	13-1	avi		Pie	A:	00/	inte	x 5%	deb	cS			·	
	B3-4	Δ		Pigo	<u>3.9</u>		intact	5%	deb	rS				
	B3/	3					, " " " " " " " " " " " " " " " " " " "							
3	c3-4	マク												
	E3-4	NV						,						
	E3-1	ND			A									
	c3-1	NO			/		•						_	
	B3-4	CM											-	Rev 3-2009

Laboratory name:	REI
instrument	JEOL 100 N S
Voltage (KV)	100 KV
Magnification	20KX 10KX
Grid opening area (mm2)	0.011
Scale: 1L =	0.28 um
Scale: 1D =	0.056 um
Primary filter area (mm2)	385
Secondary Filter Area (mm2)	
QA Type	

RIR
A
496
8/25/11
219459
786511

Fraction of primary filter used	
Total Resuspension Volume (ml)	
Volume Applied to secondary filter (ml)	

Analyzed by	1K
Analysis date	9/6/11
Method (D=Direct, I=Indirect, IA=Indirect, ashed)	D
Counting rules (ISO, AHERA, ASTM)	A 14
Grid storage location	Month Analyzed
Scope Alignment	Date Analyzed

Grid	Grid Grid Opening Str		No. of Structures		Dimensions		Identification	Mineral Class				1 = yes, blank = no		
On the	Gild Opening	Туре	Primary	Total	Length	Wkith	Identification	Amphibole	С	NAM	Sketch/Comments	Sketch	Photo	EDS
A	H4-3	40												
	(94-3	ND			•	·								
	F4-3	Ou											·	
	25-6	ND					· · · · · · · · · · · · · · · · · · ·							
	C5-6	ND			Br	ep A	270%	intact	5-	7/. 1	Pebris			
3	25-4	ND		•										
	C5-4	MD												
	B5-4	M									·			
	86-4	M								, _				
	C6-4	M			8v	ep B	~A	1	en	ln.	76/11			

Laboratory name:	REI
Instrument	JEOL 100 N(S)
Voltage (KV)	100 KV
Magnification	(20B)X 10KX
Grid opening area (mm2)	0.011
Scale: 1L =	0.28 um
Scale: 1D =	0.056 um
Primary filter area (mm2)	385
Secondary Filter Area (mm2)	
QA Type	

RAR.
A
872
8-26-11
219459
786512

F-Factor Calculation (Indirect Pr	reps Only):
Fraction of primary filter used	
Total Resuspension Voluma (ml)	
Volume Applied to secondary filter (ml)	

Analyzed by	AL
Analysis date	8-30-11
Method (D=Oirect, I=Indirect,	5
IA=indirect, ashed)	
Counting rules (ISO, AHERA, ASTM)	Ahora
Grid storage location	Month Analyzed
Scope Alignment	Date Analyzed

N

Grid	Grid Opening	Structure	No. of St	ructures	Dimensions		Identification	Mineral Class				1 = yes, blank = no		
		Туре	Primary	Total	Length	Width	identification	Amphibole	С	NAM	Sketch/Comments	Sketch	Photo	EDS
A	F3-6	Δ												
	F3-3	\mathcal{N}								·				
	E3.6	5		Prec	A:	75%	intac	<i>t</i> 3-5	4	Je b	\sim			
	E3.3	2		Pisa	B	95%	intac	t 3.5	of di	eba				
	C3-6	MD												
B	F3-4	MD						/						
	F3-1	MD				X								
	E3-4	M												
	E3-1	W												
		÷						ī. ·						

Laboratory name:	REI
Instrument	JEOL 100 N(S)
Voltage (KV)	100 KV
Magnification	(20B)X 10KX
Grid opening area (mm2)	0.011
Scale: 1L =	0.28 um
Scale: 1D =	0.056 um
Primary filter area (mm2)	385
Secondary Filter Area (n:m2)	
QA Tyoe	

ROR
A
874
8-26-11
219459
786513

Analyzed by	AH
Analysis date	8-30-11
Method (D=Dlrect, l=Indlrect, IA=Indirect, ashed)	D
Counting rules (ISO, AHERA, ASTM)	Ahora
Grid storage location	Month Analyzed
Scope Alignment	Date Analyzed

F-Factor Calculation (Indirect Pi	reps Only):
Fraction of primary filter used	
Total Resuspension Volume (ml)	
Volume Applied to secondary filter (ml)	

Grid	Grid Opening	Stmcture	No. of St	ructures	Dime	nsions	Identification Mineral Class		· ·				1 = yes, blank = no		
		Туре	Primary	Total	Length	Width	Identification	Amphibole	С	NAM	Sketch/Comments	Sketch	Photo	EDS	
A	F3-4	<u>av</u>											·		
	F3-1	20			·									<i>:</i>	
	E34	\triangle		P	2 A	: 60	guint	act 5	9/40	le 6	25				
	E3-1	\sqrt{D}		P	e o B	7	% inf	aet 5	4	le 60	5				
	E2-3	ND						-							
B	63-4	ND													
	63-1	ay		,				$\widehat{}$							
	F3-4	ay													
	F3-)	$\sqrt{2}$													
	£34	MD			/										

Laboratory name:	REI
Instmment	JEOL 100 (B) S
Voltage (KV)	100 KV
Magnification	20kx 10kx
Grid opening area fmm2)	0.011
Scale: IL =	0.28 um
Scale: 1D =	0.056 um
Primary filter area (mm2)	385
Secondary Filter Area (mm2)	
QA Type	·

Client :	RAR
Sample Type (A=Air, D=Dust):	A
Air volume (L) or dust area (cm2)	874
Date received by lab	8-26-11
Lab Job Number:	219459
Lab Sample Number:	786514

F-Factor Calculation (Indirect Preps Only):					
Fractian of primary filter used					
Total Resuspension Volume (ml)	·				
Volume Applied to secondary filter (ml)					

Analyzed by	NO
Analysis date	8/31/11
Method (D=Direct, I=Indirect, IA=Indirect, ashed)	4
Counting rules (ISO, AHERA, ASTM)	Ahera
Grid storage location	Month Analyzed
Scope Alignment	Date Analyzed

Grid	Grid Opening	Structure	No. of Structures		Dimensions		Identification	Mineral Class			1 = yes, blank = no			
O.I.G	Ond Opening	Туре	Primary	Total	Length	Width	Identinoation	Amphibole	С	NAM	Sketch/Comments	Sketch	Photo	EDS
A	HS-4	MD												
	65-4	_ M_												
	F5-4	_NO_		,							·			
	E5-4	ng												
	C5-4	MO		60-	751	To	es of	57.0eb	65					
B	HH-41	MD									. •			
	64-4	ΔΩ			A									
	F4 -4	M												
	E4-4	M							_					

Laboratory name:	REI
Instrument	JEOL 100(N) S
Voltage (KV)	100 KV
Magnification	(20)(X 10)(X
Grid opening area (mm2)	0.011
Scale: 1L =	0.28 um
Scale: 1D =	0.056 um
Primary filter area (mm2)	385
Secondary Filter Area (mm2)	
QA Type	

Client :	RAR
Sample Type (A=Air, D=Dust):	A
Air volume (L) or dust area (cm2)	874
Date received by lab	8-26-1
Lab Job Number	219459
Lab Sample Number:	786515

Analyzed by	ND
Analysis date	8/31/11
Method (D=Direct, I=Indirect, IA=Indirect, ashed)	4
Counting rules (ISO, AHERA, ASTM)	Ahera
Grid storage locatkın	Month Analyzed
Scope Alignment	Date Analyzed

F-Factor Calculation (Indirect P	reps Only):
Fraction of primary filter used	
Total Resuspension Volume (ml)	
Volume Applied to secondary filter (ml)	

Grid	Grid Opening	Structure	No. of Structures		Dimensions		Identification	Mineral Class				1 = yes, blank = no		
One	Cina Opening	Туре	Primary	Total	Length	Width		Amphibole	С	NAM	Sketch/Comments	Sketch	Photo	EDS
A	#3-3	M-												
	63-3	100		•				·						
	F3-3	MP				·								
	E3-3	M												
	C3-3	NO		5	0:	30	y.In	hot 5	2, 6	elon	5			
	B3-3	ND												
B	46-4	N			•									
	66-4	NO												
	F6-4	MP												
									·					20v S. 2000

Laboratory name:	REI
Instrument	JEOL 100 (N)S
Voltage (KV)	100 KV
Magnification	(2015X 1016X
Grid opening area (mm2)	0.011
Scale: 1L =	0.28 um
Scale: 1D =	0.056 um
Primary filler area (mm2)	385
Secondary Filter Area (mm2)	
QA Type	·

Client :	RaR
Sample Type (A=Air, D=Dust):	A
Air volume (L) or dust area (cm2)	888
Date received by lab	8-26-11
Lab Job Number:	219459
Lab Sample Number	786516
	- .

1000 00	1 1000
F-Factor Calculation (Indirect Pr	reps Only):
Fraction of primary filter used	
Total Rasuspenskm Volume (ml)	
Volume Applied to secondary litter (ml)	

Analyzed by	JB.
Analysis date	8/3/11
Method (D=Direct, I=Indirect,	7
(A=Indirect, ashed)	12
Counting rules (ISO, AHERA, ASTM)	Aheron
Grid storage location	Month Analyzed
Scope Alignment	Date Analyzed

Grid	Grid Grid Opening Structur		No. of Structures		Dimensions		Identification	Mineral Class				1 = y	es, blank	= no
Grid Opening	Туре	Primary	Total	Length	Width		Amphibole	С	NAM	Sketch/Comments	Sketch	Photo	EDS	
A	£4-4	M											·	
	64-1	W				Pry	A	07 unh	nf		3-5% d	low	5	
	4-4	M				Por	6	20 % in 1	mf		3-5%	elm	<u>, </u>	
	C5-1	M					,		_/		1			
13	F4-4	12							B	1 81	31/a			
	F4-4	M								' /	/			· · ·
	04-4	w												·
	C3-4	M												
·						·				·				

Laboratory name:	REI
Instrument	JEOL 100 (N) S
Voltage (KV)	100 KV
Magnification	(20kgx iokgx
Grid opening area (mm2)	0.011
Scale: 1L =	0.28 um
Scale: 1D =	0.056 um
Primary filter area (mm2)	385
Secondaiy Filter Area (mm2)	
QA Type	

Client :	RaR
Sample Type (A=Air, D=Dust):	A
Air volume (L) or dust area (cm2)	884
Date received by lab	8-26-1
Lab Job Number:	219459
Lab Sample Number:	786517

Analysis date	8/31
Method (D=Oirect, I=Indirect, IA=Indirect, ashed)	7
Counting rules (ISO, AHERA, ASTM)	Ahero
Grid storage location	Month Analyz
Scope Alignment	Date Analyze

Analyzed by

F-Factor Calculation (Indirect P	reps Only):
Fraction of primary filter used	
Total Resuspension Volume (ml)	
Volume Applied to secondary filter (ml)	

l	Grid	Grid Opening	Structure	No. of Structures		s Dimensions		Identification	Mineral Class			.	1 = yes, blank = no		
			Туре	Primary	Total	Length	Width	1 .	Amphibole	С	NAM	Sketch/Comments	Sketch	Photo	EDS
	A	15-1	M		•				·				·		:
	·	15-1	M												
	·	H5-1	W)				m	A &	Dhink	nt	5	70/2 de	ms	× .	
	·	615-1	N			\mathcal{A}		B 80	Phein G	nt	5-	7 % de	SWS		
		F5-1	W				(1R	1	sh				
	<u>B</u>	G15-1	MÓ						1-40		7				
		F5-1	M												
		E5-1	M							·					
											·				

	
Laboratory name:	REI
Instrument	JEOL 100/N)S
Voltage (KV)	100 KV
Magnification	(2015X 1015X
Grid opening area (mm2)	0.011
Scale: 1L =	0.28 um
Scale: 1D =	0.056 um
Primary filter area (mm2)	385
Secondary Filter Area (mm2)	
QA Type	·

RaR
A
884
8-26-1
219459
786518

Lab Sample Number:	786518
F-Factor Caleulation (Indirect Pr	eps Only):
Fraction of primary litter used	·
Total Resuspension Volume (ml)	
Volume Applied to secondary filter (ml)	

Analyzed by	JB
Analysis dale	8/31/4
Method (D=Dlrect, l=Indirect,	
IA=Indirect, ashed)	
Counting mles	Δ/
(ISO, AHERA, ASTM)	Their
Grid storege location	Month Analyzed
Scope Alignment	Date Analyzed

Grid	Grid Grid Opening Structure		No. of St	ructures	Dime	nsions	Identification	Minerei Class				1 = y	es, blank	c = no
	Grid Opening	Туре	Primary	Total	Length	Width		Amphibole	С	NAM	Sketch/Comments	Sketch	Photo	EDS
A	K4-3	M		<u> </u>										
	1-4-3	M				Pin	o A	90 hin	m	f	5-7%	Lon	25	
	64-3	M				Pm	03	90%	hu	+	5-7%	lo br	25	
	F4-3	W							, ·	1				
3	64-6	M				<u>.</u>		19		d	31/4			· ·
	F4-6	ΔM		_ <u>.</u>						/	1			
	E4-6	W)						/						
	C4-3	M												· ·
						·								

Laboratory name:	REI
Instrument	JEOL 100/N S
Voltage (KV)	100 KV
Magnification	(20KX 10KX
Grid opening area (mm2)	0.011
Scale: 1L =	0.28 um
Scale: 1D =	0.056 um
Primary filter area (mm2)	385
Secondary Filter Area (mm2)	
·	
QA Type	L

Client :	RAR
Sample Type (A=Air, D=Dust):	A
Air volume (L) or dust area (cm2)	880
Date received by lab	8-26-1
Lab Job Number:	219459
Lab Sample Number:	786519

F-Factor Calculation (Indirect Pr	reps Only):						
Fraction of primary filter used							
Total Resuspension Volume (ml)							
Volume Applied to secondary filtar (ml)							

Analyzed by	15
Analysis date	8/31/11
Method (D=Direct, I=Indirect, IA=Indirect, ashed)	人 区
Counting mles (ISO, AHEFIA, ASTM)	Ahera
Grid storage location	Month Analyzed
Scope Alignment	Date Analyzed

Grid	Grid Opening	Structure	No. of St	ructures	Dime	nsions	Identification	Mineral Class				1 = yes, blank =		= no
		Type	Primary	Total	Length	Width		Amphibole	С	NAM	Sketch/Comments	Sketch	Photo	EDS
A	44-1	M				<u> </u>								
	(94-)	MD			F	n	A	Of nota	it	5-	7 horale	w5	•	
	F4-1	M		· · · · · · · · · · · · · · · · · · ·) I	15 8	Ochemb	int	5	7% dels	وكمه		
	F4-1	W		·		1			4		, ,			·
B	14-1	NO						1	Sul	Zh.	de			
	K4-1	NO		,·					l	//				
	14-1	W						, /						
	(94-1	M												
					٠.	_					2			
				·					·					

Laboratory name:	REI
Instrument	JEOL 100 N S
Voltage (KV)	100 KV
Magnification	(20xx 10KX
Grid opening area (mm2)	0.011
Scale: 1L =	0.28 um
Scale: 1D =	0,056 um
Primary filter area	385
Secondary Filter Area (mm2)	
QA Type	

RAR
A
916
8-26-1
219459
786520

Analyzed by	JB
Analysis date	8311
Method (D=Direct, l=Indirect, IA=Indirect, ashed)	D
Counting rules (ISO, AHERA, ASTM)	Ahera
Grid storage location	Month Analyzed
Scope Alignment	Date Analyzed

F-Factor Calculation (Indirect Preps Only):						
Fraction of primary filter used						
Total Resuspension Volume (ml)						
Volume Applied to secondary filler (mi)						

Grid	Grid Opening	Strncture	No. of St	mctures	Dirizensions Identif		Dirizensions Identifica		Dirizensions Identification Mineral Class					1 = yes, blank = no		
		Туре	Primary	Total	Length	Width		Amphibole	c	NAM	Sketch/Comments	Sketch	Photo	EDS		
A	K3-6	$\Delta \Delta \Delta$					Į.	~						: •		
	H3-6	NO				mosp	A	10/0 m	Lears	- 3	3-5% d	bur	5			
	613-6	CM			6	2	9 8	00/2 M	hul	4 3	-5 % de	bre	5			
	F3-6	CM				<i>I</i> ,			sh		11					
13	84-4	w			·			4	Ber	1	& pola		·			
	44-4	MD									/ /-		,	· .		
	644	W												j		
	F4-4	M					•									
								·								

Laboratory name:	REI
Instrument	JEOL 100(N)S
Voltage (KV)	100 KV
Magnification	(20KX 10KX
Grid opening area (mm2)	0.011
Scale: 1L =	0.28 um
Scale: 1D =	0.056 um
Primary filter area (mm2)	385
Secondary Filter Area (mm2)	
QA Type	

Client :	RAR
Sample Type (A=Alr, D=Dust):	A
Air volume (L) br dust area (cm2)	916
Date received by lab	8-26-11
Lab Job Number:	219459
Lab Sample Number:	786521

F-Factor Calculation (Indirect Pr	eps Only):
Fraction of primary filter used	
Total Resuspension Volume (ml)	
Volume Applied to secondary filter (ml)	

Analyzed by	1331
Analysis date	8/31/11
Method (D=Direct, l=Indirect, IA=Indirect, ashed)	757
Counting mles	Alam
(ISO, AHERA, ASTM)	Muse
Grid storage location	Month Analyzed
Scope Alignment	Date Analyzed

Grid	Grid Opening	Structure	No. of Structures		Dimensions		Identification	Mineral Class			1 = yes, blank = no			
	January Politing	Туре	Primary	Total	Length	Width	idonan-jadon	Amphibole	С	NAM	Sketch/Comments	Sketch	Photo	EDS
A	K5-1	M												
	145-1	W					o A	90 % in.	funt		3-5% d	bus		
	65-1	m			Í	n	06	90%	Lu	F 3	-5% de	bus		
·	F5-1	M												
B	K6-1	W		·				Bu	5	31/4				
1	46-1	W)						7						
	G6-1	W					/							
	F6-1	M												

	T
Laboratory name:	REI
Instrument	JEOL 106 N S
Voltage (KV)	100 KV
Magnification	(20kx 10kx
Grid opening area (mm2)	0.011
Scale: 1L =	0.28 um
Scale: 1D =	0.056 um
Primary filter area (mm2)	385
Secondary Filter Area (mm2)	
QA Туре	

Client:	RAR
Sample Type (A=Air, D=Dust):	A.
Air volume (L) or dust area (cm2)	892
Date received by lab	8-26-1
Lab Job Number:	219459
Lab Sample Number:	786522

F-Factor Calculation (Indirect Preps Only):						
Fraction of primary filter used						
Total Resuspension Volume (ml)						
Volume Applied to secondary filter (ml)	<u> </u>					

Analyzed by	JB
Analysis date	3/31/11
Method (D=Direct, I=Indirect, IA=Indirect, ashed)	2
Counting rules (ISO, AHERA, ASTM)	Ahera
Grid storage locabon	Month Analyzed
Scope Alignment	Date Analyzed

Grid	Grid Opening	Structure	No. of Structures		Dimensions		Identification	Mineral Class			1 = yes, blank = no			
		Туре	Primary	Total	Length	Width		Amphibole	С	NAM	Sketch/Comments	Sketch	Photo	EDS
A	65-4	M									·			
	F5-4	٠.٨				Pm	A	70% in	furt		3-5% d	bu'	9	
\	£5-4	ND				Pr	B-	A		7	,			
	C5-4	\sim						1B	1	4/31	lu .			
B	144-4	M						1		7-7				
	64-4	W												·
	F4-4	W)									·			
	E4-4	M					·							
		ĺ												•

Laboratory name:	REI
Instrument	JEOL 100 N 9
Voltage (KV)	100 KV
Magnification	(20KX 10KX
Grid opening area (mm2)	0.011
Scale: 1L =	0,28 um
Scale: 1D =	0.056 um
Primary filter area (mm2)	385
Secondary Filter Area (mm2)	335
QA Type	
MAY 13he	<u> </u>

RaR
A
908
8-26-1
219459
786523

Analyzed by	JB
Analysis date	8/31/11
Method (D=Direct, I=Indirect, IA=Indirect, ashed)) b'
Counting rules (ISO, AHERA, ASTM)	Aheron
Grid storage location	Month Analyzed
Scope Alignment	Date Analyzed

F-Factor Calculation (Indirect Preps Only):					
Fraction of primary filter used					
Total Resuspension Volume (ml)	·				
Volume Applied to secondary filter (ml)					

Grid	Grid Opening	Structure Type	No. of Structures		Dimensions		Identification	Mineral Class		,	1 = yes, blank = no			
			Primary	Total	Length	Width		Amphibole	С	NAM	Sketch/Comments	Sketch	Photo	EDS
A	444	W				<	1							
	644	W				Rujo	A	Olambe	mit	2	-5% del	w`s		
	F4-4	W		·		· · · · ·					·			
	144	W)				Pn	\$ 80	Vin Lu	nf		3-5% Nove	bris	S	
6	H4-3	M		,						A	11			·."
	64-3	M								Di	1 431	d		
'	F4-3	M												
	E4-3	w						7			,			

Rev 3-2009

Analytical Procedures - AHERA

Transmission electron microscopy/energy dispersive X-ray spectrometry/selected area electron diffraction (TEM/EDX/SAED) was employed in the analysis of the samples, which were collected on 25 mm mixed cellulose ester air filters. A portion of each filter was collapsed with acetone and etched in a plasma asher. The etched filter was then coated with a thin layer of carbon in a carbon side down. The sample was then placed inside a condensation washer and treated with acetone to remove the filter matrix and expose any inert material.

For each sample, enough grid openings on a 200 mesh TEM grid are analyzed to ensure an analytical sensitivity of at least 0.005 structures/cc. A minimum of four grid openings from two preparations are analyzed for each sample. The grid openings are searched for fibrous structures which, if present are analyzed by SAED and/or EDX (elemental analysis). The AHERA protocol requires SAED confirmation of enough chrysotile asbestos structures on each sample to cause the sample to exceed 70 structures/mm² (usually 4 or 5 structures). Both SAED and EDX confirmation are required of enough amphibole structures on each sample to cause the sample to exceed 70 structures/mm² (usually 4 or 5 structures) per sample. Either SAED or EDX is required for the remaining asbestos structures of either type. The morphology of each structure is determined and the length and the diameter of any asbestos structures are recorded. Asbestos fibers, bundles, cluster and matrices were identified and recorded. The asbestos structures have been defined in AHERA as follows:

Fiber: is a structure having a minimum length greater than or equal to 0.5

micron with an aspect ratio of 5:1 or greater with substantially parallel

sides.

Bundle: is a structure composed of three or more fibers in parallel arrangement,

with each fiber closer than the diameter of one fiber.

Cluster: is a structure with fibers in random arrangements such that all fibers are

intermixed and no single fiber is isolated from the group.

Matrix: is a fiber or fibers with one end free and the other end embedded or

hidden by a particulate. The exposed fiber end must meet the fiber

definition given above.

If more than 50 asbestos structures are identified and confirmed on a sample, AHERA analysis may be terminated after completion of the grid opening, which contains the 50th structure. AHERA protocol requires the laboratory to reject any clearance sample which contains in excess of 25% total particulate loading or which appears to be unevenly loaded.

The AHERA protocol includes specific sampling requirements, including minimum numbers of samples and minimum air volumes. Specifically, the 70 structures/mm² clearance criteria is only allowed for sets five inside samples (collected in a group of 13 samples including: five outsides and three blanks) with volumes greater than 1200 liters (40 CFR Part 763, page 41894). Deviation from the AHERA sampling protocol may affect the validity of the analytical results. Analysis of samples collected by non-protocol methods are not accredited by NVLAP

Equations Used for Calculations

Area Analyzed, mm² = # GO counted x Average GO Area (mm)

Concentration, $s/cc = \frac{\# \text{ Asbestos Structures}}{\# \text{ GO Counted}} \times \frac{1}{\text{Volume (L)}} \times \frac{\text{Eff. Filter Area (mm}^2)}{\text{Average GO area (mm}^2)} \times \frac{1L}{1000cc}$

Filter loading, $s/mm^2 = \frac{\# Asbestos strucmres}{Area Analyzed (mm^2)}$

GO = TEM grid opening